



Issue date: 01/05/2015

Safety Data Sheet

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier Sky
Product name Metered Fragrance
Product Code 8011,8012,8013,8014,8015,8016,8017,8018,8019,8020

Other means of identification

Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.
Uses advised against Do not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier :

Sky Systems Co. Inc.
1825 Taylor Place
Ontario, CA 91761
909-923-7040

Emergency Telephone Number

Company Phone Number 800-451-3444
Emergency telephone ChemTel 800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL
Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves, protective clothing, eye protection and face protection.
Keep away from heat, sparks, open flames and hot surfaces. — No smoking
Pressurized container: Do not pierce or burn, even after use
Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

-

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.
Chemical Family MIXTURES.
Formula 7-8175

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact	In case of contact, immediately flush skin with plenty of water. Wash skin with soap and water. If irritation develops, consult a physician.
inhalation	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.
INGESTION	Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

Most important symptoms and effects, both acute and delayed

Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label directions for correct installation and placement of dispenser. Store cans in a cool, dry place away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation and placement of dispenser. Store cans in a cool, dry place away from heat and open flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Aerosol		
Appearance	Clear liquid that will be aerosolized.	Odor	Perfumed.
Color	Color will vary depending on the perfume in the product.	Odor threshold	No information available
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not applicable	Solvent-based product.	
Melting point/freezing point	Not applicable	No information available	
Boiling point/boiling range	Acetone 133 F/56.29 C	No information available	
Flash Point	This is an aerosol product for which Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.	No information available	
	Faster than butyl acetate	No information available	
Evaporation Rate		No information available	
Flammability (solid, gas)		No information available	
Flammability Limits in Air		No information available	
Upper flammability limits	Not available		
Lower Flammability Limit	Not available		
Vapor pressure		No information available	
Vapor Density		No information available	
Specific gravity	0.86 g/ml	No information available	
Water solubility	Insoluble in water	No information available	
Solubility in other solvents		No information available	
Partition coefficient		No information available	
Autoignition Temperature		No information available	
Decomposition temperature		No information available	
Kinematic viscosity		No information available	
Dynamic viscosity		No information available	
Explosive properties	No information available		
Oxidizing properties	No information available		
<u>Other Information</u>			
Softening point	No information available		
Molecular weight	No information available		
VOC content (%)	29.63		
Density	7.16 lb/gal		
Bulk Density	No information available		

10. Stability and Reactivity

Reactivity

Not applicable
no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product Information	This product has not been tested as whole. See below for information on ingredients.
inhalation	no data available.
Eye Contact	no data available.
Skin contact	no data available.
INGESTION	no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg (Rat) = 4200 µL/kg (Rabbit)	> 5240 mg/m ³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation and reddening after prolonged or repeated contact with skin.
Serious eye damage/eye irritation	Irritating to eyes.
irritation	May cause skin and eye irritation.
corrosivity	Not applicable.
sensitization	No information available.
Germ Cell Mutagenicity	No information available.
carcinogenicity	Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.
Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity	-
The following values are calculated based on chapter 3.1 of the GHS document .	
ATEmix (oral)	4755 mg/kg
ATEmix (dermal)	31248 mg/kg
ATEmix (inhalation-gas)	10804 mg/l
ATEmix (inhalation-dust/mist)	15 mg/l
ATEmix (inhalation-vapor)	78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Diethylene Glycol Monoethyl Ether 111-90-0		10000: 96 h Lepomis macrochirus mg/L LC50 static 19100 - 23900: 96 h Lepomis macrochirus mg/L LC50 flow-through 11400 - 15700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 11600 - 16700: 96 h Pimephales promelas mg/L LC50 flow-through 13400: 96 h Salmo gairdneri mg/L LC50 flow-through		3940 - 4670: 48 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 2.2: 96 h Lepomis macrochirus mg/L LC50 static		4720: 96 h Den-dronereides heteropoda mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002

Chemical name

California Hazardous Waste Status

Acetone
67-64-1

Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener
UN/ID no UN1950
Proper Shipping Name Limited quantity (LQ)
Hazard Class 2.1
Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	X		X
N-Butane 106-97-8	X	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

<u>NFPA</u>	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department
Issue date Jan-05-2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet